



Model no. ON-DC17-IR/ON-DC17H-IR



Features:

- Vandal resistant withstand 10 pounds sledgehammer
- Water resistant pass IP 66



Model no.	ON-DC17-IR	ON-DC17H-IR
No Of Effective Pixels(H) /(N)	500(H)×582(V)	752(H)×582(V)
Resolution(TV lines) (H)/(N)	380 TVL	480
Electronic Shutter	Auto 1/60~1/100000 Sec. (NTSC)	Auto 1/50~1/100000 Sec.(PAL)
Synchronizing System	Internal	
White balance	Auto (2500K ~9500K)	
Pick Device	1/3" Color CCD Sony	
Gamma Correction	0.45	
Minimum Illumination	1.0Lux/F1.8 IR:0 Lux ON	1.2 Lux/F1.8 IR:0 Lux on
S/N Ratio	More Than 48dB	
Scanning System	2:1 Interlace	
Video Output	1 Vp-p 75 ohm, BNC Connector	
Storage Temperature	-30°C ~ 80°C	
Working Temperature	-10°C ~ 50°C	
Backlight Compensation	Yes	
SIZE	105(dia) * 85 (H) mm	
Lens Mount	6.0mm F1.8	
Power Source	DC 12V 1A	
Effective Distance	20M	
Beam Angle	90 degree	
Detective Angle	30 degree	
Power Consumption	Total: DC12V, typical 260mA, Camera : DC 12V, typical 100mA IR LED Projecting lighter: DC12V, typical 160mA	
IR LED	21pcs	

